



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> : <b>G06K 19/06</b>	<b>A1</b>	(11) International Publication Number: <b>WO 93/08542</b> (43) International Publication Date: <b>29 April 1993 (29.04.93)</b>
(21) International Application Number: <b>PCT/US92/08903</b> (22) International Filing Date: <b>19 October 1992 (19.10.92)</b> (30) Priority data: <b>780,639</b> <b>23 October 1991 (23.10.91)</b> <b>US</b> (71)(72) Applicant and Inventor: <b>YUEN, Henry, C. [US/US];</b> <b>P.O. Box 1159, Redondo Beach, CA 90278 (US).</b> (74) Agent: <b>PROUT, D., Bruce; Christie, Parker &amp; Hale, 350</b> <b>West Colorado Boulevard, Suite 500, Pasadena, CA</b> <b>91109 (US).</b> (81) Designated States: <b>AT, AU, BB, BG, BR, CA, CH, CS,</b> <b>DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG,</b> <b>MN, MW, NL, NO, PL, RO, RU, SD, SE, US, European</b> <b>patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT,</b> <b>LU, MC, NL, SE), OAPI patent (BF, BJ, CF, CG, CI,</b> <b>CM, GA, GN, ML, MR, SN, TD, TG).</b>		<b>Published</b> <i>With international search report.</i>

## (54) Title: BAR CODE MATRIX TELEVISION CALENDAR

SATURDAY JULY 20, 1991									
12	10	7:30	8:00	8:30	9:00	9:30	10:00	10:30	11:00
ROSSIN'S HEROES	DOWN HOME	GOLDEN GIRLS	EMPTY NEST	DEAR JOHN	SATURDAY NIGHT LIVE				
MOVIE "THE WILD LIFE" (1984)	MOVIE "THE RETIRED FOREST" (COLORIZED) (1936)				NEWS-McDONNICK, PEREZ		CHEERS		
MOVIE "KING KONG" (1976) JEFF BRIDGES, JESSICA LANGE	CHARLES GORDON (PG)				NEWS- ATTENBERY DASILVA		(PG) ARSENIO WALKER "GUEST" STEVE WINWOOD; DEREK CHARLES ROSSMO. (REPEAT)		
A LAMER	SOUTH BANK SHOW		MOVIE "FRIDA" (1985) OFELIA MEDINA, JUAN JOSE GURGOLA		MOVIE "THE WOMAN IN QUESTION" (1980)				
MOVIE "FERRIS BUZZER'S DAY OFF" (1986)	MOVIE "BLUE THUNDER" (1983) ROY SCHNEIDER, MALCOLM McDOWELL (PG)		MOVIE "THE SIGNATURE" (1981) KATHY THOMPSON, OWA SHAW (PG)		TALES/ CRYPT		BEST OF ROBERT TOWNSEND		
MOVIE "DAYS OF THUNDER" (1989) (PG-13)	MOVIE "DOUBLE CRISSED" (1981) DENNIS HOPPER, ROBERT CROUCH								

## (57) Abstract

A television calendar arranged in a channel/time of day matrix for combined visual selection of programs for direct viewing and for use in automatic recording of programs for future viewing having a vertical column of bar codes that are encoded to represent and arranged adjacent to a vertical column of channel indicators and having a horizontal row of bar codes that are encoded to represent and arranged adjacent to a horizontal row of time of day indicators for the start of a television program. The arrangement of channels vertically and time of day horizontally can be reversed. A template overlay of just the vertical and horizontal bar codes can be used with a normal television program arranged in a matrix with a separate listing of day of month bar codes. Alternatively, the day of month bar code can be printed on every page of the television program arranged in a matrix and used with the template overlay of the vertical and horizontal bar codes.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	LJ	Liechtenstein	SK	Slovak Republic
CI	Côte d'Ivoire	LK	Sri Lanka	SN	Senegal
CM	Cameroon	LU	Luxembourg	SU	Soviet Union
CS	Czechoslovakia	MC	Monaco	TD	Chad
CZ	Czech Republic	MG	Madagascar	TG	Togo
DE	Germany	ML	Mali	UA	Ukraine
DK	Denmark	MN	Mongolia	US	United States of America
ES	Spain			VN	Viet Nam
FI	Finland				

## BAR CODE MATRIX TELEVISION CALENDAR

5

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

10

This invention relates to bar code readers used to timer preprogram a videocassette recorder (VCR) to record a particular television program.

## 2. Prior Art

15

20

25

30

VCRs with a bar code programming (BCP) feature were introduced several years ago. The ideal situation is to print a bar code, representing the Channel, Date, Time and Length information (CDTL information), next to each television program. Anyone wishing to tape a given television program would then draw the bar-code reader across the corresponding bar code and the VCR would be automatically set to tape the television program. However, no regularly distributed publications (television guides, cable guides or newspapers) print the bar code next to each program, or any significant fraction of the programs listed. The reason is that a bar code containing the CDTL information could be 2 to 3 inches long with a height of 1/3 to 1/2 inch. In order to print a bar code next to each television program, a large amount of space would have to be allocated. With the large number of television programs and the high cost of publication, this proposition is economically unfeasible.

35

^ 35

Instead, BCP sellers distribute a sheet containing separate groups of bar codes for the channel, date, time and length, and require the user to first look up from a television program listing the CDTL information, then enter it by drawing the bar-code reader across appropriate segments in the bar-code sheet.

This process is tedious because it involves both the television guide and the bar-code sheet, and requires a significant amount of eye-hand translation and coordination.

5           Some sellers of BCP distribute a limited quantity of pamphlets with bar codes for a limited selection of shows. Using these sheets, the user can achieve the original objective of entering the show for taping with one step. Unfortunately, the coverage and quantity of these pamphlets are not sufficient to  
10           make BCP popular.

          One particular VCR with bar code programming is the Panasonic PV-4020, manufactured by Matsushita Corp., Toyko, Japan, which allows 4 separate unattended recordings over a one  
15           month time period to be programmed with a bar code scanner.

          To use the Panasonic PV-4020 bar scanner, a mode selector switch is set to the "SCANNER" position and the clock on the VCR is set to the correct time. Then the program to be  
20           preprogrammed is looked up by the user in a regular television program listing. Then the scanner power button is pressed "ON", and the user traces from a separate bar code programming sheet, the date, the start time, the stop time and the channel. The bar  
25           code programming sheet has bar codes for each possible day of a month (1-31), each possible start time 12 AM to 11 PM with minutes in 5 minute intervals, each possible stop time in the same format, and bar codes for each possible channel (00 to 99). When all information is entered correctly, multiple beeps are  
30           heard from the scanner. Then the user can point the scanner at the VCR and press the transmit button to send the scanned date, start time, stop time and channel to the VCR. The VCR will give a series of confirmation beeps. Then a 15 second display of the program contents will appear on the TV screen. The program  
35           transmitted can be cleared by pressing the Clear button while it is displayed.

If the program was not entered correctly, a message to that effect appears on the TV screen for 15 seconds when the Transmit button is pressed. The user then scans a "CLEAR" bar code on the programming sheet and then re-enters the program by tracing the date, start time, stop time, and channel bar codes again. When the codes are properly entered the user turns the scanner Power button "OFF", which sets the VCR for timer programming.

The user can also record at the same time every day by scanning the EVERY DAY bar code, or the user can record at the same time on the same day of each week by scanning the EVERY WEEK bar code.

If the user wishes to check the programming then the user can press the Check button on the Bar Code Scanner. The entire program will be displayed on the TV screen and the first program will flash. If the user continues to press the check button, each program number will flash in turn. If the Check button is pressed when the 4th program number is flashing, then the on screen display will return to normal TV channel reception. In the check mode, when a program is flashing, it can be cancelled by pressing the Clear button on the Bar Code Scanner.

As is evident from the prior description the prior art for bar code programming is cumbersome, because it requires the user to manually select the proper bar codes from a separate bar code sheet for the selected program and requires a significant amount of eye-hand translation and coordination.

#### SUMMARY OF THE INVENTION

This invention is a novel means of formatting the television guides so that bar code information can be conveniently displayed for the users of bar code programming (BCP) without occupying

significant space and therefore rendering the widespread printing of bar-code information economically feasible.

5       The contemplated format allows CDTL information in the form of bar codes to be integrated with a television guide so that it can be intuitively and easily read by the BCP user and to permit the bar-coded information to be directly and intuitively related to every show shown in a grid format of the television guide so that the user does not have to go to a separate bar-code sheet to  
10       retrieve this information.

      The bar codes and programs are arranged in a row-column layout with channel bar codes arranged along the column headings and time of day bar codes arranged along the row headings or visa  
15       versa. A bar code for the day of the month is located anywhere on the sheet. Also a program length table of bar codes can be provided on the sheet or the start time of day of the next program on the same channel can be scanned to derive the time of day to terminate recording. The length information can be  
20       absolute or additive, such that the user scans a bar code representing the absolute time, such as 3 hours or for additive time scans a bar code representing 1 hour three times, resulting in a total of three hours.

25       In certain situations, the print quality of the bar codes may be too demanding for normal newspapers. It may be more efficient to use a single template which can employ durable material and high quality printing for each television magazine, which when placed over the television program grid can provide  
30       the CDTL information. The date information can be printed on every page in the television guide near the television program grid with a large enough print, because it is printed only once for each day. The television program grid with the date on every page would be used in conjunction with a template with the  
35       channel bar codes and the time of day bar codes. Alternately,

the date could be scanned from a separate list of "days of the week" or "days of the month".

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the invention and its advantages will be apparent from the detailed description taken in conjunction with the accompanying drawings in which:

10

FIG. 1a is a television program calendar of the present invention showing the placement of bar codes along a channel axis and a time axis to allow a user to preprogram a VCR to record a program.

15

FIG. 1b is a bar code table to allow a user to specify program length.

20

FIG. 2 is a bar code table to allow a user to specify the recording of a program every week on the day selected.

FIG. 3 is a bar code to allow a user to specify the recording of a program every day.

25

FIG. 4 is a bar code to allow a user to clear a program that has been preprogrammed for recording.

FIG. 5 illustrates the scanning of a bar code with a bar code scanner.

30

FIG. 6 illustrates the transmission of a program from a bar code scanner (FIG. 6b) to a VCR (FIG. 6a).

35

FIG. 7 illustrates an on screen display for confirming the transmitted program.

FIG. 8 illustrates an on screen display for checking and/or clearing preprogrammed programs.

5 FIG. 9 illustrates a template overlay for bar code programming with the time on the horizontal axis and the channels on the vertical axis.

10 FIG. 10 illustrates a template overlay for bar code programming with the channels on the horizontal axis and the time on the vertical axis.

FIG. 11 illustrates a bar code table to allow a user to specify the date for recording.

15 FIG. 12 is a television program calendar with the date bar code printed on the television calendar, which would be used along with a template overlay for bar code programming with time bar codes on the horizontal axis and the channel bar codes on the vertical axis, as shown in FIG. 9.

20

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings, and more particularly, to  
25 FIG. 1, there is shown a matrix bar code calendar 10 of the present invention. The leftmost column is a vertical column of channel bar codes 12 and the upper row is a horizontal row of time of day bar codes 14, which correspond to and represent the vertical listing of channel indicators 16 and horizontal listing  
30 of time of day indicators 18, respectively. The program descriptors 20 are arranged within the matrix bar code calendar 10, so that they are properly aligned with the channel indicators 16 and the program start times indicated by the time of day indicators 18. With each matrix bar code calendar 10 is a date  
35 indicator 22, a component of which is the day of the month



indicator 26. For FIG. 1, the date indicator 22 is Saturday July 20, 1991. The day of the month indicator 26 is the 20th day of July. Along side the date indicator 22 is a day of month bar code 24, which represents the day of the month indicator 26.

5

The matrix bar code calendar 10 could also have a length of program bar code table 30, which consists of a set of length of program indicators 32 calibrated in hours and corresponding set of length of program bar codes 34. There can also be a set of  
10 length of program indicators 36 calibrated in minutes and corresponding length of program bar codes 38.

To scan in a program, using, for example, the Panasonic PV-4020, the user would identify the program to record by looking  
15 at matrix bar code calendar 10. Suppose the user has selected Blue Thunder, starting at 9:00 and ending at 10:30 on channel CMAX. Then the user would use a scanner 50, such as that shown in FIG. 6a, in the manner shown in FIG. 5 to scan particular bar codes 51. The scan start point is indicated in FIG. 5 as scan  
20 start point 52. While scanning the bar codes the user would press the scanner on button 56 on scanner 50. This activates bar code reading lamp 54.

To preprogram a VCR for recording the movie Blue Thunder 39,  
25 shown in FIG. 1, the user would first scan the day of month bar code 24 and then the start time of day bar code 40. The next bar code to be scanned depends on how the system operates. If the stop time of day is desired then stop time of day bar code 42 could be scanned, which is the time of day for the next program  
30 on the same channel. For some systems, such as the Panasonic PV-4020, the length of the program is the desired input, rather than the stop time of day. The length of the program could be supplied by scanning length of program in hours bar code 43 followed by the length of program in minutes bar code 44, as  
35 shown in FIG. 1b. The last item to be scanned would be the

channel, which would be obtained by scanning the channel bar code 41, which represents CMAX.

Thus, the user never has to leave the matrix bar code calendar 10, because all the information that is needed is conveniently arranged for the user. Once the proper bar codes are all scanned, the user points the scanner 50 at the video cassette recorder (VCR) 70, as shown in FIGs. 6a and 6b, and presses the transmit button 58. If the program has been entered properly, then the television connected to the VCR will show an on screen display for confirming the VCR programming, such as that shown in FIG. 7 showing transmitted program information 74. The television will show transmitted program information 74 for a short while and then return to the normal television channel. If the program hasn't been properly entered, then a warning is displayed on the television and the user can clear the bar scanner by scanning clear bar code 48, shown in FIG. 4, and then rescanning the program bar codes.

If the user wishes to check the programs that have been preprogrammed for recording, then the user presses the check button 60 on scanner 50, which will cause a television connected to the VCR to show the on screen display for checking and/or clearing preprogrammed programs 76, as shown in FIG. 8. The first program will flash and if the user wishes to cancel the program, then the user does so by pressing clear button 62. The user can scroll between programs by continuing to press check button 60. After the last program, the last press of check button 60 will return the television to the normal channel.

It is possible for the user to specify that a program will be recorded every week at the same time, which is useful for weekly serials, by scanning a day of week bar code 46 representing and corresponding to a day of week indicator 45, as shown in FIG. 2. It is also possible for the user to specify

The day of month bar code 24 could be printed directly on the television calendar for each day and on every page, as shown in FIG. 12, because it is printed only once for each day and therefore can have large enough print. This avoids possible problems with printing quality. This calendar would be used along with a template, such as that shown in FIG. 9, which would provide the vertical channel bar codes 82 and the horizontal time of day bar codes 84. Another advantage of this type of calendar is that it would remind the user that bar code programming is available by the prominent display of the day of month bar code. The user would scan the bar codes for the day of month, the channel, the start time and the stop time, which would be the same as the start time for the succeeding program on the same channel. Alternately, the length of program could be entered by scanning the appropriate bar codes FIG. 1b, the bar code table for length of the program.

It is thought that the present invention and many of its attendant advantages will be understood from the foregoing description and it will be apparent that various changes may be made in the form, construction and arrangement of the parts thereof and in the methods used without departing from the spirit and scope of the invention or sacrificing all of its material advantages, the forms hereinbefore described being merely a preferred or exemplary embodiments thereof.

CLAIMS

I claim:

1 1. A television calendar for combined visual selection of  
2 programs for direct viewing and for use in automatic recording of  
3 programs for future viewing, the combination comprising:

4 a vertical column of channel indicators having a  
5 channel indicator for each channel in said television calendar;  
6 a horizontal row of time of day indicators having a  
7 time of day indicator for each time of day in said television  
8 calendar;

9 a plurality of programs each having a corresponding  
10 program descriptor, a corresponding channel, and a corresponding  
11 time of day for the start of said program;

12 wherein for each of said programs said corresponding  
13 program descriptor is arranged vertically in alignment with said  
14 channel indicator in said vertical column of channel indicators  
15 that matches said corresponding channel of said program;

16 wherein for each of said programs said corresponding  
17 program descriptor is arranged horizontally in alignment with  
18 said time of day indicator in said horizontal row of time of day  
19 indicators that matches said corresponding time of day for the  
20 start of said program;

21 a vertical column of bar codes that are encoded to  
22 represent said vertical column of channel indicators and arranged  
23 adjacent to said vertical column of channel indicators;

24 a horizontal row of bar codes that are encoded to  
25 represent said horizontal row of time of day indicators and  
26 arranged adjacent to said horizontal row of time of day  
27 indicators; and

28 a day of the month bar code representing the day of the  
29 month of said program.

1 2. A television calendar for combined visual selection of

that a program will be recorded every day at the same time, which is useful for daily soaps, by scanning an everyday bar code 47, as shown in FIG. 3.

5           As indicated before, the print quality of the bar codes may be too demanding for normal newspapers. It may be more efficient to use a matrix bar code calendar overlay 80, such as shown in FIG. 9, which can employ durable material and high quality printing and which when placed over the television calendar grid  
10           can provide the CDTL information. On overlay 80, vertical channel bar codes 82 are placed in a column corresponding to the channel indicators 86, and horizontal time of day bar codes 84 are placed in a row corresponding to the time of day indicators 88. The overlay of FIG. 9 is shown with the channels 86 and time  
15           of days 88 printed on the overlay; however, they are not necessary as long as the user understands how to align the overlay and the television calendar, which would be arranged the same as FIG. 1, but without the vertical column of channel bar codes 12 and the horizontal row of time of day bar codes 14. If  
20           the day of month bar code 24 is also not printed, then a day of month table, as shown in FIG. 11, with day of month indicators 100 and corresponding day of month bar codes 102 would be provided to allow the day of the month to be scanned.

25           It is possible that the overlay and the television calendar could be arranged as shown in FIG. 10, which has vertical time of day bar codes 92 and horizontal channel bar codes 94 corresponding to and representing the time of day indicators 96 and channel indicators 98, respectively. This arrangement could  
30           also be applied to matrix bar code calendar 10. Note that by convention the codes are shown in FIG. 1a across the top of the calendar and the vertical codes are on the left side of the television calendar; however, they could just as easily have been across the bottom and at the right side of the television  
35           calendar.

2 programs for direct viewing and for use in automatic recording of  
3 programs for future viewing, the combination comprising:

4           a vertical column of time of day indicators having a  
5 time of day indicator for each time of day in said television  
6 calendar;

7           a horizontal row of channel indicators having a channel  
8 indicator for each channel in said television calendar;

9           a plurality of programs each having a corresponding  
10 program descriptor, a corresponding channel, and a corresponding  
11 time of day for the start of said program;

12           wherein for each of said programs said corresponding  
13 program descriptor is arranged vertically in alignment with said  
14 time of day indicator in said vertical column of time of day  
15 indicators that matches said corresponding time of day for the  
16 start of said program;

17           wherein for each of said programs said corresponding  
18 program descriptor is arranged horizontally in alignment with  
19 said channel indicator in said horizontal row of channel  
20 indicators that matches said corresponding channel of said  
21 program;

22           a vertical column of bar codes that are encoded to  
23 represent said vertical column of time of day indicators and  
24 arranged adjacent to said vertical column of time of day  
25 indicators;

26           a horizontal row of bar codes that are encoded to  
27 represent said horizontal row of channel indicators and arranged  
28 adjacent to said horizontal row of channel indicators; and

29           a day of the month bar code representing the day of the  
30 month of said program.

1 3.   A television calendar for combined visual selection of  
2 programs for direct viewing and for use in automatic recording of  
3 programs for future viewing of claim 1 or claim 2 further comprising:

4 a bar code table having a plurality of time length  
5 indicators and a plurality of corresponding bar codes for varying  
6 time lengths of said programs.

1 4. A system for the automatic recording of a television program  
2 on a recorder comprising:

3 a television calendar visually listing television  
4 programs arranged as a vertical column of channel indicators  
5 having a channel indicator for each channel in said television  
6 calendar, a horizontal row of time of day indicators having a  
7 time of day indicator for each time of day in said television  
8 calendar, a plurality of programs each having a corresponding  
9 program descriptor, a corresponding channel, and a corresponding  
10 time of day for the start of said program and wherein for each of  
11 said programs said corresponding program descriptor is arranged  
12 vertically in alignment with said channel indicator in said  
13 vertical column of channel indicators that matches said  
14 corresponding channel of said program and wherein for each of  
15 said programs said corresponding program descriptor is arranged  
16 horizontally in alignment with said time of day indicator in said  
17 horizontal row of time of day indicators that matches said  
18 corresponding time of day for the start of said program, a  
19 vertical column of bar codes that are encoded to represent said  
20 vertical column of channel indicators and arranged adjacent to  
21 said vertical column of channel indicators, a horizontal row of  
22 bar codes that are encoded to represent said horizontal row of  
23 time of day indicators and arranged adjacent to said horizontal  
24 row of time of day indicators, and a day of the month bar code  
25 representing the day of the month of said program;

26 a bar code scanner for scanning bar codes corresponding  
27 to a television program representing the channel for said  
28 program, a time of day for the start of said program, a time of  
29 day for the end of said program by scanning the time of day for  
30 the start of the next program on the same channel, and a day of

31 the month for said program; and  
32 a means for automatically controlling recording of  
33 television signals by a recorder comprising means for receiving  
34 representations of the bar codes via said bar code scanner from  
35 the television calendar and for enabling such recorder to  
36 commence recording television signals carrying the program on the  
37 channel, on the day of the month, starting at the time and ending  
38 at the time represented by said scanned bar codes.

1 5. A system for the automatic recording of a television program  
2 on a recorder comprising:

3 a television calendar visually listing television  
4 programs arranged as a vertical column of time of day indicators  
5 having a time of day indicator for each time of day in said  
6 television calendar, a horizontal row of channel indicators  
7 having a channel indicator for each channel in said television  
8 calendar, a plurality of programs each having a corresponding  
9 program descriptor, a corresponding channel, and a corresponding  
10 time of day for the start of said program and wherein for each of  
11 said programs said corresponding program descriptor is arranged  
12 vertically in alignment with said time of day indicator in said  
13 vertical column of time of day indicators that matches said  
14 corresponding time of day for the start of said program and  
15 wherein for each of said programs said corresponding program  
16 descriptor is arranged horizontally in alignment with said  
17 channel indicator in said horizontal row of channel indicators  
18 that matches said corresponding channel for said program, a  
19 vertical column of bar codes that are encoded to represent said  
20 vertical column of time of day indicators and arranged adjacent  
21 to said vertical column of time of day indicators, a horizontal  
22 row of bar codes that are encoded to represent said horizontal  
23 row of channel indicators and arranged adjacent to said  
24 horizontal row of channel indicators, and a day of the month bar  
25 code representing the day of the month of said program;



26 a bar code scanner for scanning bar codes corresponding  
27 to a television program representing the channel for said  
28 program, a time of day for the start of said program, a time of  
29 day for the end of said program by scanning the time of day for  
30 the start of the next program on the same channel, and a day of  
31 the month for said program; and

32 a means for automatically controlling recording of  
33 television signals by a recorder comprising means for receiving  
34 representations of the bar codes via said bar code scanner from  
35 the television calendar and for enabling such recorder to  
36 commence recording television signals carrying the program on the  
37 channel, on the day of the month, starting at the time and ending  
38 at the time represented by said scanned bar codes.

1 6. The system for the automatic recording of a television  
2 program on a recorder of claim 4 or claim 5 further comprising:

3 a bar code table having a plurality of time length  
4 indicators and a plurality of corresponding bar codes for varying  
5 time lengths of said programs.

1 7. A method of creating a television calendar for combined  
2 visual selection of programs for direct viewing and for use in  
3 automatic recording of programs for future viewing, comprising  
4 the steps of:

5 creating a vertical column of channel indicators having  
6 a channel indicator for each channel in said television calendar;  
7 creating a horizontal row of time of day indicators  
8 having a time of day indicator for each time of day in said  
9 television calendar;

10 positioning a plurality of programs each having a  
11 corresponding program descriptor, a corresponding channel, and a  
12 corresponding time of day for the start of said program wherein  
13 for each of said programs said corresponding program descriptor

14 is arranged vertically in alignment with said channel indicator  
15 in said vertical column of channel indicators that matches said  
16 corresponding channel of said program and wherein for each of  
17 said programs said corresponding program descriptor is arranged  
18 horizontally in alignment with said time of day indicator in said  
19 horizontal row of time of day indicators that matches said  
20 corresponding time of day for the start of said program;  
21           creating a vertical column of bar codes that are  
22 encoded to represent said vertical column of channel indicators  
23 and arranged adjacent to said vertical column of channel  
24 indicators;  
25           creating a horizontal row of bar codes that are encoded  
26 to represent said horizontal row of time of day indicators and  
27 arranged adjacent to said horizontal row of time of day  
28 indicators; and  
29           creating a day of the month bar code representing the  
30 day of the month of said program.

1 8.   A method of creating a television calendar for combined  
2 visual selection of programs for direct viewing and for use in  
3 automatic recording of programs for future viewing, comprising  
4 the steps of:

5           creating a vertical column of time of day indicators  
6 having a time of day indicator for each time of day in said  
7 television calendar;  
8           creating a horizontal row of channel indicators having  
9 a channel indicator for each channel in said television calendar;  
10          positioning a plurality of programs each having a  
11 corresponding program descriptor, a corresponding channel, and a  
12 corresponding time of day for the start of said program wherein  
13 for each of said programs said corresponding program descriptor  
14 is arranged vertically in alignment with said time of day  
15 indicator in said vertical column of time of day indicators that  
16 matches said corresponding time of day for the start of said

17 program and wherein for each of said programs said corresponding  
18 program descriptor is arranged horizontally in alignment with  
19 said channel indicator in said horizontal row of channel  
20 indicators that matches said corresponding channel of said  
21 program;

22           creating a vertical column of bar codes that are  
23 encoded to represent said vertical column of time of day  
24 indicators and arranged adjacent to said vertical column of time  
25 of day indicators;

26           creating a horizontal row of bar codes that are encoded  
27 to represent said horizontal row of channel indicators and  
28 arranged adjacent to said horizontal row of channel indicators;  
29 and

30           creating a day of the month bar code representing the  
31 day of the month of said program.

1 9.   The method of creating a television calendar for combined  
2 visual selection of programs for direct viewing and for use in  
3 automatic recording of programs for future viewing of claim 7 or  
4 claim 8 further comprising the step of:

5           creating a bar code table having a plurality of time  
6 length indicators and a plurality of corresponding bar codes for  
7 varying time lengths of said programs.

1 10.   A television calendar on a display medium for combined  
2 visual selection of programs for direct viewing and for use in  
3 automatic recording of programs for future viewing, the  
4 combination comprising:

5           a vertical column of channel indicators having a  
6 channel indicator for each channel in said television calendar;

7           a horizontal row of time of day indicators having a  
8 time of day indicator for each time of day in said television calendar  
9           a plurality of programs each having a corresponding

10 program descriptor, a corresponding channel, and a corresponding  
11 time of day for the start of said program;

12           wherein for each of said programs said corresponding  
13 program descriptor is arranged vertically in alignment with said  
14 channel indicator in said vertical column of channel indicators  
15 that matches said corresponding channel of said program;

16           wherein for each of said programs said corresponding  
17 program descriptor is arranged horizontally in alignment with  
18 said time of day indicator in said horizontal row of time of day  
19 indicators that matches said corresponding time of day for the  
20 start of said program;

21           a vertical column of bar codes that are encoded to  
22 represent said vertical column of channel indicators and arranged  
23 adjacent to said vertical column of channel indicators;

24           a horizontal row of bar codes that are encoded to  
25 represent said horizontal row of time of day indicators and  
26 arranged adjacent to said horizontal row of time of day  
27 indicators; and

28           a day of the month bar code representing the day of the  
29 month of said program.

1 11. A television calendar on a display medium for combined  
2 visual selection of programs for direct viewing and for use in  
3 automatic recording of programs for future viewing, the  
4 combination comprising:

5           a vertical column of time of day indicators having a  
6 time of day indicator for each time of day in said television  
7 calendar;

8           a horizontal row of channel indicators having a channel  
9 indicator for each channel in said television calendar;

10           a plurality of programs each having a corresponding  
11 program descriptor, a corresponding channel, and a corresponding  
12 time of day for the start of said program;

13           wherein for each of said programs said corresponding

14 program descriptor is arranged vertically in alignment with said  
15 time of day indicator in said vertical column of time of day  
16 indicators that matches said corresponding time of day for the  
17 start of said program;

18           wherein for each of said programs said corresponding  
19 program descriptor is arranged horizontally in alignment with  
20 said channel indicator in said horizontal row of channel  
21 indicators that matches said corresponding channel of said  
22 program;

23           a vertical column of bar codes that are encoded to  
24 represent said vertical column of time of day indicators and  
25 arranged adjacent to said vertical column of time of day  
26 indicators;

27           a horizontal row of bar codes that are encoded to  
28 represent said horizontal row of channel indicators and arranged  
29 adjacent to said horizontal row of channel indicators; and

30           a day of the month bar code representing the day of the  
31 month of said program.

1 12. A television calendar on a display medium for combined  
2 visual selection of programs for direct viewing and for use in  
3 automatic recording of programs for future viewing of claim 10 or  
4 claim 11 further comprising:

5           a bar code table having a plurality of time length  
6 indicators and a plurality of corresponding bar codes for varying  
7 time lengths of said programs.

1 13. A method of creating a television calendar on a display  
2 medium for combined visual selection of programs for direct  
3 viewing and for use in automatic recording of programs for future  
4 viewing, comprising the steps of:

5           creating a vertical column of channel indicators having  
6 a channel indicator for each channel in said television calendar;

7           creating a horizontal row of time of day indicators  
8 having a time of day indicator for each time of day in said  
9 television calendar;  
10           positioning a plurality of programs each having a  
11 corresponding program descriptor, a corresponding channel, and a  
12 corresponding time of day for the start of said program wherein  
13 for each of said programs said corresponding program descriptor  
14 is arranged vertically in alignment with said channel indicator  
15 in said vertical column of channel indicators that matches said  
16 corresponding channel of said program and wherein for each of  
17 said programs said corresponding program descriptor is arranged  
18 horizontally in alignment with said time of day indicator in said  
19 horizontal row of time of day indicators that matches said  
20 corresponding time of day for the start of said program;  
21           creating a vertical column of bar codes that are  
22 encoded to represent said vertical column of channel indicators  
23 and arranged adjacent to said vertical column of channel  
24 indicators;  
25           creating a horizontal row of bar codes that are encoded  
26 to represent said horizontal row of time of day indicators and  
27 arranged adjacent to said horizontal row of time of day  
28 indicators; and  
29           creating a day of the month bar code representing the  
30 day of the month of said program.

1 14. A method of creating a television calendar on a display  
2 medium for combined visual selection of programs for direct  
3 viewing and for use in automatic recording of programs for future  
4 viewing, comprising the steps of:

5           creating a vertical column of time of day indicators  
6 having a time of day indicator for each time of day in said  
7 television calendar;  
8           creating a horizontal row of channel indicators having  
9 a channel indicator for each channel in said television calendar;

10           positioning a plurality of programs each having a  
11 corresponding program descriptor, a corresponding channel, and a  
12 corresponding time of day for the start of said program wherein  
13 for each of said programs said corresponding program descriptor  
14 is arranged vertically in alignment with said time of day  
15 indicator in said vertical column of time of day indicators that  
16 matches said corresponding time of day for the start of said  
17 program and wherein for each of said programs said corresponding  
18 program descriptor is arranged horizontally in alignment with  
19 said channel indicator in said horizontal row of channel  
20 indicators that matches said corresponding channel of said  
21 program;

22           creating a vertical column of bar codes that are  
23 encoded to represent said vertical column of time of day  
24 indicators and arranged adjacent to said vertical column of time  
25 of day indicators;

26           creating a horizontal row of bar codes that are encoded  
27 to represent said horizontal row of channel indicators and  
28 arranged adjacent to said horizontal row of channel indicators;  
29 and

30           creating a day of the month bar code representing the  
31 day of the month of said program.

1 15. The method of creating a television calendar on a display  
2 medium for combined visual selection of programs for direct  
3 viewing and for use in automatic recording of programs for future  
4 viewing of claim 13 or claim 14 further comprising the step of:

5           creating a bar code table having a plurality of time  
6 length indicators and a plurality of corresponding bar codes for  
7 varying time lengths of said programs.

1 16. An overlay on a display medium for use in automatic  
2 recording of programs for future viewing comprising:

3           a vertical column of bar codes that are encoded to  
4 represent channels and arranged for placement adjacent to a  
5 vertical column of channel indicators on a television program;  
6 and

7           a horizontal row of bar codes that are encoded to  
8 represent time of day for the start of television programs and  
9 arranged for placement adjacent to a horizontal row of time of  
10 day indicators on a television program.

1 17. An overlay on a display medium for use in automatic  
2 recording of programs for future viewing comprising:

3           a vertical column of bar codes that are encoded to  
4 represent time of day for the start of television programs and  
5 arranged for placement adjacent to a vertical column of time of  
6 day indicators on a television program; and

7           a horizontal row of bar codes that are encoded to  
8 represent channels and arranged for placement adjacent to a  
9 horizontal row of channel indicators on a television program.

1 18. The overlay on a display medium for use in automatic  
2 recording of programs for future viewing of claim 16 or claim 17  
3 further comprising:

4           a bar code table having a plurality of time length  
5 indicators and a plurality of corresponding bar codes for varying  
6 time lengths of said programs.

1 19. A method of creating an overlay on a display medium for use  
2 in automatic recording of programs for future viewing comprising:

3           creating a vertical column of bar codes that are  
4 encoded to represent channels and arranged for placement adjacent  
5 to a vertical column of channel indicators on a television  
6 program; and



7           creating a horizontal row of bar codes that are encoded  
8 to represent time of day for the start of television programs and  
9 arranged for placement adjacent to a horizontal row of time of  
10 day indicators on a television program.

1 20. A method of creating an overlay on a display medium for use  
2 in automatic recording of programs for future viewing comprising:

3           creating a vertical column of bar codes that are  
4 encoded to represent time of day for the start of television  
5 programs and arranged for placement adjacent to a vertical column  
6 of time of day indicators on a television program; and

7           creating a horizontal row of bar codes that are encoded  
8 to represent channels and arranged for placement adjacent to a  
9 horizontal row of channel indicators on a television program.

1 21. The method of creating an overlay on a display medium for  
2 use in automatic recording of programs for future viewing of  
3 claim 19 or claim 20 further comprising:

4           creating a bar code table having a plurality of time  
5 length indicators and a plurality of corresponding bar codes for  
6 varying time lengths of said programs.

1 22. A system for the automatic recording of a television program  
2 on a recorder comprising:

3           a television calendar on a display medium visually  
4 listing television programs arranged as a vertical column of  
5 channel indicators having a channel indicator for each channel in  
6 said television calendar, a horizontal row of time of day  
7 indicators having a time of day indicator for each time of day in  
8 said television calendar, a plurality of programs each having a  
9 corresponding program descriptor, a corresponding channel, and a  
10 corresponding time of day for the start of said program and

11 wherein for each of said programs said corresponding program  
12 descriptor is arranged vertically in alignment with said channel  
13 indicator in said vertical column of channel indicators that  
14 matches said corresponding channel of said program and wherein  
15 for each of said programs said corresponding program descriptor  
16 is arranged horizontally in alignment with said time of day  
17 indicator in said horizontal row of time of day indicators that  
18 matches said corresponding time of day for the start of said  
19 program, and a day of the month bar code representing the day of  
20 the month of said program;

21           an overlay on a display medium having a vertical column  
22 of bar codes that are encoded to represent channels and arranged  
23 for placement adjacent to a vertical column of channel indicators  
24 on a television program and having a horizontal row of bar codes  
25 that are encoded to represent time of day for the start of  
26 television programs and arranged for placement adjacent to a  
27 horizontal row of time of day indicators on a television program;

28           a bar code scanner for scanning bar codes corresponding  
29 to a television program representing the channel for said  
30 program, a time of day for the start of said program, a stop time  
31 for said program, and a day of the month for said program; and

32           a means for automatically controlling recording of  
33 television signals by a recorder comprising means for receiving  
34 representations of the bar codes via said bar code scanner from  
35 the television calendar and for enabling such recorder to  
36 commence recording television signals carrying the program on the  
37 channel, on the day of the month, starting at the start time and  
38 stopping at the stop time represented by said scanned bar codes.

1 23. A system for the automatic recording of a television program  
2 on a recorder comprising:

3           a television calendar on a display medium visually  
4 listing television programs arranged as a vertical column of time

5 of day indicators having a time of day indicator for each time of  
6 day in said television calendar, a horizontal row of channel  
7 indicators having a channel indicator for each channel in said  
8 television calendar, a plurality of programs each having a  
9 corresponding program descriptor, a corresponding channel, and a  
10 corresponding time of day for the start of said program and  
11 wherein for each of said programs said corresponding program  
12 descriptor is arranged vertically in alignment with said time of  
13 day indicator in said vertical column of time of day indicators  
14 that matches said corresponding time of day for the start of said  
15 program and wherein for each of said programs said corresponding  
16 program descriptor is arranged horizontally in alignment with  
17 said channel indicator in said horizontal row of channel  
18 indicators that matches said corresponding channel for said  
19 program, and a day of the month bar code representing the day of  
20 the month of said program;

21           an overlay on a display medium having a vertical column  
22 of bar codes that are encoded to represent time of day for the  
23 start of television programs and arranged for placement adjacent  
24 to a vertical column of time of day indicators on a television  
25 program and having a horizontal row of bar codes that are encoded  
26 to represent channels and arranged for placement adjacent to a  
27 horizontal row of channel indicators on a television program;

28           a bar code scanner for scanning bar codes corresponding  
29 to a television program representing the channel for said  
30 program, a time of day for the start of said program, a stop time  
31 for said program, and a day of the month for said program; and

32           a means for automatically controlling recording of  
33 television signals by a recorder comprising means for receiving  
34 representations of the bar codes via said bar code scanner from  
35 the television calendar and for enabling such recorder to  
36 commence recording television signals carrying the program on the  
37 channel, on the day of the month, starting at the start time and  
38 stopping at the stop time represented by said scanned bar codes.

1 24. The system for the automatic recording of a television  
2 program on a recorder of claim 22 or claim 23 further comprising:  
  
3           a bar code table having a plurality of time length  
4 indicators and a plurality of corresponding bar codes for varying  
5 time lengths of said programs.




*Fig. 1b*

LENGTH		43 (HRS)	36 (MIN)
32 1:00	▷	20	▷
30 2:00	▷	25	▷
30 3:00	▷	30	▷
4:00	▷	35	▷
5:00	▷	40	▷
6:00	▷	45	▷


*Fig. 2*

EVERY WEEK	
45 SU	▷
MO	▷
TU	▷
WE	▷
TH	▷
FR	▷
SA	▷


*Fig. 3*




*Fig. 4*




*Fig. 5*





*Fig. 6a*



*Fig. 6b*



*Fig. 7*

74


PROG. 1  
DATE 12 MON  
START 10:00 PM  
STOP 11:00 PM  
CH 2  
  
TO ERASE PUSH CLEAR

*Fig. 8*


76

1 12 10:00P 11:00P 02  
2 -- --:-- --:-- --  
3 TV 8:30A 9:00A 08  
4 DAY 8:00P 9:00P 12  
  
NEXT PROG....CHECK KEY

*Fig. 9*



*Fig. 10*


































*Fig. 11*

*DATE*

*102*

*100* {

<i>1</i>	▷		<i>16</i>	▷	
<i>2</i>	▷		<i>17</i>	▷	
<i>3</i>	▷		<i>18</i>	▷	
<i>4</i>	▷		<i>19</i>	▷	
<i>5</i>	▷		<i>20</i>	▷	
<i>6</i>	▷		<i>21</i>	▷	
<i>7</i>	▷		<i>22</i>	▷	
<i>8</i>	▷		<i>23</i>	▷	
<i>9</i>	▷		<i>24</i>	▷	
<i>10</i>	▷		<i>25</i>	▷	
<i>11</i>	▷		<i>26</i>	▷	
<i>12</i>	▷		<i>27</i>	▷	
<i>13</i>	▷		<i>28</i>	▷	
<i>14</i>	▷		<i>29</i>	▷	
<i>15</i>	▷		<i>30</i>	▷	
			<i>31</i>	▷	

9/9

Fig. 12


SATURDAY JULY 20, 1991 <sup>20</sup> 22

18	7:30	8:00-8:30	9:00	9:30	10:00	10:30	11:00
4	ROGGIN'S HEROES	DOWN HOME	EMPTY NEST ~20	DEAR JOHN ~20		SATURDAY NIGHT LIVE	
5	MOVIE ~ "THE WILD LIFE" (1984)	MOVIE "THE PETRIFIED FOREST" (COLORIZED) (1936)		NEWS-McCORMICK, PEREZ ~20		CHEERS	
13	MOVIE ~ "JEFF BRIDGES, JESSICA LANGE, (1976) "KING KONG"	MOVIE ~ "FRIDA" (1985) OFELIA MEDINA, JOHN JOSE GUERRA		NEWS- ATTEBERY DASILVA		(21) ARSENIO HALL - "GUEST: STEVE WINWOOD, DEREK, CHARLES KORSMO. (REPEAT)	
BRNO	D. LANDER	SOUTH BANK SHOW	MOVIE ~ "FRIDA" (1985) OFELIA MEDINA, JOHN JOSE GUERRA			MOVIE ~ "THE WOMAN IN QUESTION" (1950)	
CHAX	MOVIE ~ "FERRIS BUELLER'S DAY OFF" (1986)		MOVIE ~ "BLUE THUNDER" (1938) ROY SCHEIDER, MALCOLM McDOWELL. (R)			MOVIE ~ "CAPTIVITY" (1987) KEVIN THOMPSON, OWA SIMMS (R)	
HBO	MOVIE ~ "DAYS OF THUNDER" (1990) (PG-13)		MOVIE ~ "DOUBLE-CROSSED" (5) (1991) DENNIS HOPPER, ROBERT CARRADINE			TALES/ CRYPT	BEST OF ROBERT TOWNSEND

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 92/08903

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>6</sup>		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 G06K19/06		
<b>II. FIELDS SEARCHED</b>		
Minimum Documentation Searched <sup>7</sup>		
Classification System	Classification Symbols	
Int.Cl. 5	G06K	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched <sup>8</sup>		
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup></b>		
Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
X	PATENT ABSTRACTS OF JAPAN vol. 13, no. 578 (E-864)20 December 1989 & JP,A,12 41 923 ( NIPPON DENSO CO.LTD ) 26 September 1989 see abstract ---	1,4,7, 10,13, 16,19,22
A	EP,A,0 254 518 (MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.) 27 January 1988 see page 2, line 11 - page 5, line 25 see figures 1-6 ---	2,5,8, 11,14, 17,20,23
A	PATENT ABSTRACTS OF JAPAN vol. 12, no. 273 (E-639)29 July 1988 & JP,A,63 052 524 ( MITSUBISHI ELECTRIC CORP ) 5 March 1988 see abstract ---	2,5,8, 11,14, 20,23
-/--		
<sup>9</sup> Special categories of cited documents: <sup>10</sup> "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such docu- ments, such combination being obvious to a person skilled in the art. "A" document member of the same patent family		
<b>IV. CERTIFICATION</b>		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
19 JANUARY 1993	04.02.93	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	LAPEYRONNIE P.F.J. 	

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
A	<p>PATENT ABSTRACTS OF JAPAN vol. 12, no. 234 (E-629) 5 July 1988 &amp; JP,A,63 27 128 ( MATSUSHITA ELECTRIC IND CO LTD. ) 4 February 1988 see abstract</p> <p>-----</p>	1

US 9208903  
SA 66043

19/01/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0254518	27-01-88	JP-A- 63026791	04-02-88
		JP-A- 63027128	04-02-88
		AU-A- 7579887	28-01-88
-----			

EPO FORM 10479

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82